


UWP

Mini slide plate, self lubricating



Product discription:

Mini slide plate, self lubricating

Article properties:

Sliding speed v	30 m/min
Base Material	Special Brass (SO#50SP2)
Self-lubricating	Yes
Lubricant	Graphite
Surface Pressure P	100 N/mm ²
P*v-value	200 N/mm ² x m/min
Operating temperature	-50°C / +200°C (max. 300°C)
Friction coefficient	0,07

Variants:

Articlenumber	Article name	Width W	Length L	Height H	I1	I2	M (ISO 10642)	Type
27018050	UWP 18-50	18	50	5	20	-	2xM6	A
27018075	UWP 18-75	18	75	5	45	-	2xM6	A
27018100	UWP 18-100	18	100	5	70	-	2xM6	A
27018150	UWP 18-150	18	150	5	60	-	3xM6	B
27028050	UWP 28-50	28	50	5	20	-	2xM8	A
27028075	UWP 28-75	28	75	5	45	-	2xM8	A
27028100	UWP 28-100	28	100	5	70	-	2xM8	A
27028150	UWP 28-150	28	150	5	60	-	3xM8	B
27038050	UWP 38-50	38	50	5	20	-	2xM8	A
27038075	UWP 38-75	38	75	5	45	-	2xM8	A
27038100	UWP 38-100	38	100	5	70	-	2xM8	A
27038150	UWP 38-150	38	150	5	60	-	3xM8	B
27048075	UWP 48-75	48	75	5	45	-	2xM8	A
27048100	UWP 48-100	48	100	5	70	-	2xM8	A
27048125	UWP 48-125	48	125	5	95	-	2xM8	A
27048150	UWP 48-150	48	150	5	60	-	3xM8	B
27075075	UWP 75-75	75	75	5	45	45	2xM8	C
27075100	UWP 75-100	75	100	5	70	45	2xM8	C
27075125	UWP 75-125	75	125	5	95	45	2xM8	C
27075150	UWP 75-150	75	150	5	60	45	3xM8	D
27100100	UWP 100-100	100	100	5	70	70	2xM8	C

UWP

Mini slide plate, self lubricating



Articlenumber	Article name	Width W	Length L	Height H	I1	I2	M (ISO 10642)	Type
27100125	UWP 100-125	100	125	5	95	70	2xM8	C
27100150	UWP 100-150	100	150	5	60	70	3xM8	D